

www.landforce.in



MECHANIZED AGRICULTURE FOR PRODUCTIVITY

Rotary Tiller Heavy Duty **ROBUSTO**



Rotary Tiller Heavy Duty

ROBUSTO

- ❖ Traceability upto raw material
- ❖ Every Part is Powder coated and then assembled
- ❖ Drive shaft is covered with safety covers.
- ❖ Heavy Duty Frame
- ❖ Less Maintenance Cost



A Robust design and ultimate tillage technology suitable for hard, black cotton and rocky soil. Heavy duty gear box and frame makes it strong for rough and tough conditions. The working depth can be adjusted by the height of the skids, which is easily done with the adjustment bracket on the Rotary Tillers.

TECHNICAL SPECIFICATION

Model	RTH5MG36	RTH6MG42	RTH6MG48	RTH7MG48	RTH5MG54	RTH8MG54	RTH8MG60	RTH8MG72
Size	5	6	6	7	7	8	8	9
Overall Width (inch/ Cm)	75/190	82/208	82/208	93/236	93/236	104/264	104/264	115/292
Working (inch/Cm)	60/152	69/175	69/175	78/198	78/198	87/220	87/220	105/266
Weight (inch/Cm)	505/1282	535/1358	545/1358	555/1409	565/1409	585/1485	595/1485	665/1689
Hitch Type	Cat-II							
Min HP Required	40	50	50	55	55	60	60	75
Gear Box	Multi Speed							
Side Transmission	Gear Drive							
Working Depth Min/Max	4 inch – 6 inch							
Number of Blades	36	42	48	48	54	54	60	72
PTO Speed (rpm)	540/1000							
Working Depth Control	Skids Fitted as Standard Equipment							
Rotor Speed	180-220							

**Company reserves the rights to change/amend products specifications without any prior notice.*

 www.landforce.in
 info@landforce.in
 +917837494949

DASMESH MECHANICAL WORKS
AMARGARH, DISTT- SANGRUR, PUNJAB - 148022, INDIA

landforceTM